

## ELEMENT 900 PORTRAIT

The Element 900 Portrait utilises everything spectacular in the High Efficient Element range into a more defining Portrait design. This elegant gas heater operates on Natural gas and LPG and is equipped with the best-in-class Magiglo burner. This heater is designed for an efficient combustion with up to 4.7 star rating and it maximises performance by heating up to 95m² of your space. An impressive heater with a graceful design.

### **Connecting back to Australian roots**

Element 900 Portrait is an Australian made heater that includes media options which are inspired by a collection of native Australian woodland gatherings. The rugged and rustic alpine forest media set is an added accessory that speaks of the heritage Australian forest floor.

### Versatility in installation

The heater can be fitted with a 50mm trim or a much sleeker 18mm trim that comes with a flange kit for ease of installation. Real Flame's dynamic powerflue system is utilised for a safe and efficient flueing system. Portrait can be flued up to 9 meters - horizontally, vertically or under the floor without the requirement of any polypropylene pipe. Making installation of the fireplace uncomplicated and straightforward.





### KEY SELLING FEATURES



### PORTRAIT DESIGN

The all new Portrait size in the efficient Element range.



#### ALL NEW MEDIA SET

Introducing the Alpine forest media set. Inspired by the Australian woodlands.



### **FASCIA**

Multiple fascia options. Choose between a 50mm trim or an 18mm trim with a flange kit.



### MULTIPLE FLUE INSTALLATION

with up to 13.5m flue: horizontal, vertical, or under the floor. Install 0-9m with the insulated balanced powerflue kit.



#### CHARMING FLAME PATTERNS

Portrait utilises the latest Magiglo burner to conjure an elegant flame pattern.



#### POWERFUL ROOM COVERAGE

Heats up to 95m<sup>2</sup> of room with 6.6kW output to keep those winter chills away.



### APP CONTROL


Real Flame app lets you control the fireplace remotely. App available in android and iOS devices.



### REMOTE CONTROL


Convenience of operation with a touch of a button.

# UNIT DIMENSIONS



Α	В	С	D	E	Ē	G	Н		J	K	L	М	Ν	0	Р	Q	R	S
153	<i>7</i> 6	626	475	<i>7</i> 4.5	452	472	1103	887	714	995	1007	<i>7</i> 31	101	60	46	90	50	166

## MINIMUM FRAME OUT DIMENSIONS



Α	С	D	Ε	F	G	Н	I	J	K	L	М
377	755	1295	1620	290	300	460	1500	377	159	60	230

#### NOTE

Use suitable support base, plywood not necessary.

#### Detail N

Allow min 80mm clearance for wire and gas pipe connection on the side of the framing to the unit.

If the framing is done as close to the clearance standoffs then, the timber framing must be notched to allow for the wiring and gas connection to pass.

## **SPECIFICATIONS**

APPLIANCE TYPE	High Efficiency Gas Fireplace					
STAR RATING	up to 4.7 stars					
MAX HEAT OUTPUT	up to 6.6kW					
ROOM SIZE	approx. up to 95m²					
GAS TYPE	Natural Gas	LPG				
GAS INPUT	28 High/22 Low	28 High/22 Low				

## MEDIA OPTIONS



REDGUM & COALS



LOGS & COAL



DRIFTWOOD



PEBBLES

\*4 pebble colour option(shown above - white pebbles)

## TRIM OPTIONS



50MM BLACK TRIM POWDERCOAT BLACK



18 MM TRIM POWDERCOAT BLACK \*INCLUDES FLANGE KIT FOR FLUSH WALL FINISH





Glen Dimplex Australia Pty Ltd 8 Lakeview Drive, Scoresby, VIC 3179 T 1300 554 155 E flame.care@glendimplex.com.au



Real Flame is a registered trademark of Glen Dimplex Australia Pty Ltd, all rights reserved. Authorised Real Flame Dealer

realflame.com.au